

## Screen Printing Flag

ST-110SP

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

### BRIEF DESCRIPTION

- 100% polyester warp-knitted textured fabric with semi-matte surface
- Designed for screen printing, good print through
- Perfect as flag material

### FEATURES



PVC-FREE



PHTHALATE FREE



EXCELLENT INK PENETRATION

### INK PRINTABILITY



### MATERIAL DETAILS

| PROPERTIES                     | TEST METHOD                     | METRIC                        | IMPERIAL      |
|--------------------------------|---------------------------------|-------------------------------|---------------|
| Total Weight                   | DIN EN ISO 2286-2, ASTM D751    | 110 g/sq.m                    | 3.2 oz/sq.yd  |
| Base Fabric                    | DIN 60001, ASTM D7641           | 100%polyester                 | 100%polyester |
| Weave Method                   | N/A                             | Warp-knitted                  |               |
| Shrinkage                      | 210 °C, 30s                     | ≤2%                           |               |
| Flame Resistance               | DIN 4102-1-B1, NFPA 701 Test1   | DIN 4102-1-B1, NFPA 701 Test1 |               |
| Recommend Fixation Temperature | N/A                             | 190 °C, 30s                   |               |
| Width Available                | DIN EN ISO 3759, ASTM D751-2006 | Max 320cm                     | 126"          |
| Standard Length                | DIN EN ISO 3759, ASTM D751-2006 | 100m                          | 110yds        |

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.