# Popular Flag



## ST-110T/ST-110D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

#### **BRIEF DESCRIPTION**

- 100% polyester warp-knitted textured fabric with semi-matte surface
- Perfect as flag material

### **FEATURES**







## **INK PRINTABILITY**





## **MATERIAL DETAILS**

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	110 g/sq.m	3.2 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Weave Method	N/A	Warp-knitted	
Shrinkage	210 °C, 30s	≤2%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommend Fixation Temperature	N/A	190℃-210℃, 1-2min	
Yellowing Temperature	SUPRKC REX-C400, 30s	<b>≥210</b> °C	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	100m	110yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







