

Satin Flag

ST-124T/ST-124D

BRIEF DESCRIPTION

- 100% polyester satin with high glossy finish

FEATURES



PVC-FREE



PHTHALATE FREE

INK PRINTABILITY



DYE paper



DYE direct



LATEX

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	150 g/sq.m	4.4 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Weave Method	N/A	Warp-knitted	
Shrinkage	210 °C, 30s	≤2%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommend Fixation Temperature	N/A	190°C, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.