

Super Flag

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-1101

BRIEF DESCRIPTION

- 100% polyester warp-knitted textured fabric
- High printing stability with superb ink penetration and image resolution
- Popular used as indoor & outdoor flag like national flag, company flag, etc

FEATURES



PVC-FREE



PHTHALATE FREE



EXCELLENT INK PENETRATION



WRINKLE-RESISTANT

INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	110 g/sq.m	3.2 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	210 °C, 30s	≤2%	
Tensile Strength	DIN EN ISO 1421	348x445 N/5cm	40x51 lbs/inch
Tear Strength	DIN53363	72x59 N	16x13 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190°C, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	100m	110yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.