

Voile Flag

ST-1104T/ST-1104D

BRIEF DESCRIPTION

- 100% polyester knit fabric with super light weight
- Similar to a voile, easy to "printing through" even by paper transfer
- Very convenient for transportation and installation
- Ideal for voile, partition, indoor decoration, exhibition construction, etc

FEATURES



PVC-FREE



PHTHALATE FREE



LIGHT-WEIGHT



EXCELLENT INK PENETRATION

INK PRINTABILITY



DYE paper



DYE direct



SCREEN Printing

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	50 g/sq.m	1.5 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	210 °C, 30s	≤2%	
Tensile Strength	DIN EN ISO 1421	134x393 N/5cm	15x45 lbs/inch
Tear Strength	DIN53363	24x68 N	5x15 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1,	DIN 4102-1-B1, NFPA 701 Test1,	
Recommend Fixation Temperature	N/A	190°C, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 310cm	122"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	100m	110yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.