Nightstar Blackback Pro

ST-2165T/ST-2165D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% warp-knitted polyester fabric with more white surface, blackback offers full opacity
- Extremely good anti-scratch to its black back coating and paper peeled off automatically after transfer
- Very soft hand feel and excellent crease free ability
- Slight stretch makes it easy process as backdrops, pop-up, frame, exhibition, etc

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	260 g/sq.m	7.7 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	210 °C, 30s	≤3%	
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Elasticity	Length*Width=200*50mm, Speed=100mm/min, Tension=20N	Warp: 4%	Weft: 3%
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190 ℃, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Up to 500cm	Up to 197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







