

Nova Stretch

ST-1422T/ST-1422D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- New developed stretch fabric made of 100% polyester
- Light weight but still keeps perfect opacity
- Proper elasticity in two directions and good wrinkle resistant makes stable printing & easy operation
- Ideal for light curl geometric, backdrop, trade show & grand format, etc

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	190 g/sq.m	5.6 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	210 °C, 30s	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	68%	
Elasticity	Length*Width=200*50mm, Speed=100mm/min, Tension=20N	Warp: 13% Weft: 8%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190 °C, 30s	
Width Available	DIN EN ISO 3759, ASTMD751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTMD751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.