

Aerolite Display



Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-130T/ST-130D

BRIEF DESCRIPTION

- 100% polyester fabric with semi-glossy surface
- Densely knitted with 68% opacity, flat and crease resistant
- Very good strength, perfectly used as backdrops, frontlit, banner, tradeshow display
- Compatible with dye direct and paper transfer with vivid printing color

FEATURES



PVC-FREE



PHthalate FREE



GOOD OPACITY



TIGHT STRUCTURE

INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	260 g/sq.m	7.7 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100% Polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	210°C, 30s	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	68%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190°C, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.