Heavy Knitted Display

ST-139T/ST-139D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester warp-knitted fabric with good opacity
- Truly wrinkle free, can recover quickly after folded, makes it easy for transportation
- Can be widely used as table covers, pop-up, backdrops, grandformat, etc

FEATURES







INK PRINTABILITY





MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	280 g/sq.m	8.3 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Weave Method	N/A	Warp-knitted	
Shrinkage	210 °C, 30s	≤2%	
Elasticity	Length*Width=200*50mm, Speed=100mm/min,Tension=20N	Warp:2%	Weft:5%
Shielding Rate	ANSI PH2.19, ISO 5/2	61%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190 °C, 30 s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

OEKO-TEX® CONFIDENCE IN TEXTILES

STANDARD 100

20.HCN.12564 HOHENSTEIN HTTI







