Deco Innovation



ST-115T/ST-115D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester display fabric with good opacity at light weight
- Soft & smooth, one side with textured surface while the other has silky touch
- Perfect for exhibition & event, frame & indoor deco (eg. table cloth)

FEATURES



INK PRINTABILITY



ATEX direct

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	200 g/sq.m	5.9 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Warp-knitted	
Shrinkage	210 ℃, 30s	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	(53±5)%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommend Fixation Temperature	N/A	190 ℃, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







