

Ultra White Blockout

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-208T/ST-208D

BRIEF DESCRIPTION

- Ultra white woven fabric with W/B/W structure
- Good opacity & double-sides printable
- Perfect for exhibition system, blackout, curtain, soft signage, pop-up & banner

FEATURES



PVC-FREE



PHTHALATE FREE



GOOD OPACITY



SOFT HANDFEEL

INK PRINTABILITY



DYE
paper



DYE
direct



LATEX

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	295 g/sq.m	8.6 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Woven	
Shrinkage	210 °C, 30s	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	(98±2)%	
Flame Resistance	DIN 4102-1-B1,NFPA 701 Test1, EN13501-1	DIN 4102-1-B1,NFPA 701 Test1, EN13501-1	
Recommend Fixation Temperature	N/A	190 °C, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.