

Magic Deco

ST-163T/ST-163D



Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester woven fabric with special designed textile structure
- Very high abrasion resistance, great upholstery material
- Sound absorbing fabric for a variety range of applications
- Highly recommended to be used as acoustic fabric, display system, exhibition, stage/ show/ event, stretch ceiling, upholstery fabric, home deco, etc

FEATURES



PVC-FREE



PHTHALATE FREE



HIGH TENACITY



SOFT HANDFEEL



WRINKLE-RESISTANT

INK PRINTABILITY



DYE paper



DYE direct

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	320g/sq.m	9.4 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Woven	
Shrinkage	210 °C, 30s	≤2%	
Tensile Strength	DIN EN ISO 1421	2646x1981 N/5cm	302x226 lbs/inch
Tear Strength	DIN53363	315x209 N	71x47 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1,	DIN 4102-1-B1, NFPA 701 Test1,	
Recommend Fixation Temperature	N/A	190°C,30S	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.