

# Tent Fabric



Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

## ST-301UT

### BRIEF DESCRIPTION

- 100% polyester woven fabric, 300Dx300D base with one side coated, matte
- Good water-resistance ability, perfect as tent fabric

### FEATURES



PVC-FREE



PHthalate FREE



WATER-PROOF

### INK PRINTABILITY



### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	255 g/sq.m	7.4 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Yarn Dtex	DIN EN ISO 2060, ASTM D1907	330x330 dtex	300x300denier
Weave Method	N/A	Woven	
Shrinkage	210 °C, 30s	≤3%	
Tensile Strength	DIN EN ISO 1421	1674x1117 N/5cm	191x128 lbs/inch
Tear Strength	DIN53363	285x106 N	64x24 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190°C ,30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

