

Starlight Dura

ST-6011UT

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester woven coated fabric with dense structure, more white & durable
- Truly good light transmittance without light leakage, perfect as backlit fabric
- Vivid printing colors and great ink fastness
- Also can be used as Frame System, Tents, Sun-umbrella, etc

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

| PROPERTIES | TEST METHOD | METRIC | IMPERIAL |
|--------------------------------|---------------------------------|-------------------------------|--------------|
| Total Weight | DIN EN ISO 2286-2, ASTM D751 | 190 g/sq.m | 5.6 oz/sq.yd |
| Base Fabric | DIN 60001, ASTM D7641 | 100%polyester | |
| Weave Method | N/A | Woven | |
| Shrinkage | 210°C, 30s | ≤3% | |
| Light Transmittance | ANSI PH2.19, ISO 5/2 | (45±5)% | |
| Flame Resistance | DIN 4102-1-B1, NFPA 701 Test1 | DIN 4102-1-B1, NFPA 701 Test1 | |
| Recommend Fixation Temperature | N/A | 190°C, 30s | |
| Width Available | DIN EN ISO 3759, ASTM D751-2006 | Max 500cm | 197" |
| Standard Length | DIN EN ISO 3759, ASTM D751-2006 | 50m | 55yds |

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.