

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

Dieulight Pro

ST-6091

BRIEF DESCRIPTION

- 100% polyester woven coated fabric with smooth surface, light weight
- Very good light transmittance, with no light leakage on light box
- Brilliant printing output for solvent and latex inks with good ink fastness
- Mainly used as backlit, frame fabric, also available as ceiling deco, banner, flag, etc

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	140 g/sq.m	4.1 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	
Weave Method	N/A	Woven	
Light Transmittance	ANSI PH2.19, ISO 5/2	(50±5)%	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

CONFIDENCE IN TEXTILES

STANDARD 100

20.HCN.12564 HOHENSTEIN HTTI





