

Dieulight

ST-609

BRIEF DESCRIPTION

- 100% polyester woven coated fabric with smooth surface, light weight
- Good wrinkle resistance & light transmittance, with no light leakage on light box
- Mainly used as backlit fabric on light box, also available as frame material, etc

FEATURES



PVC-FREE



PHthalate FREE



GOOD TRANSMITTANCE



LIGHT-WEIGHT

INK PRINTABILITY



UV



LATEX

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	140 g/sq.m	4.1 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	
Weave Method	N/A	Woven	
Light Transmittance	ANSI PH2.19, ISO 5/2	(48±5)%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.