Laticia Tent



Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-332UT

BRIEF DESCRIPTION

- 100% polyester fabric with 600D x 600D woven base
- Strong tensile, tear strength & water resistance feature
- Can be widely used as short-time promotion tent, parasol, outdoor event, tradeshow, etc

FEATURES



















MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	230 g/sq.m	6.8 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Yarn Dtex	DIN EN ISO 2060, ASTM D1907	660x660 dtex	600x600denier
Weave Method	N/A	Woven	
Shrinkage	210 °C, 30s	≤3%	
Tensile Strength	DIN EN ISO 1421	2065x1377 N/5cm	236x157 lbs/inch
Tear Strength	DIN53363	290x235 N	65x53 lbs
Flame Resistance	SGS	B1	
Recommend Fixation Temperature	N/A	190°C,30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







