

ST-705T/ST-705D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester top -layered textile based on a non-woven fabric
- Soft touch, ultra thickness for sound and heat insulation
- Idea material for wall covering

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	560 g/sq.m	16.5 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	210°C, 30s	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	83%	
Tensile Strength	DIN EN ISO 1421	1400x1000 N/5cm	160x114 lbs/inch
Tear Strength	DIN 53363	260x285N	58x64 lbs
Recommend Fixation Temperature	N/A	190°C, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	300cm	118"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.