Prime Textile Wall Covering



ST-703T/ST-703D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester warp-knitted wall covering with grey rough back
- High opacity & great flatness makes it perfect as wall covering even for those defect walls
- Also can be used as roll-up display, frame, art decoration material

FEATURES





INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	320 g/sq.m	9.4 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Warp-knitted 3 bar	
Shrinkage	210°C, 30s	≤3%	
Shielding Rate	ANSI PH2.19, ISO 5/2	98%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190° C, 30 s	
Width Available	DIN EN ISO 3759, ASTMD751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTMD751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







