

Diana Soft Backlit



ST-100T/ST-100D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester woven fabric with tight structure
- Smooth surface, soft hand feel, good wrinkle-resistance
- Ideal as light box, also can be used as indoor deco, display, etc

FEATURES



PVC-FREE



PHTHALATE FREE



TIGHT STRUCTURE



SOFT HANDFEEL



WRINKLE-RESISTANT

INK PRINTABILITY



DYE paper



DYE direct

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	190 g/sq.m	5.6 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Weave Method	N/A	Woven	
Shrinkage	210 °C, 30s	≤2%	
Light Transmittance	ANSI PH2.19, ISO 5/2	42%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommend Fixation Temperature	N/A	190°C, 30S	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

