



Ceiling Fabric

DT-01

Soyang's deco textile range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester warp-knitted fabric
- Always used as wall deco, ceiling fabric, etc

FEATURES



PVC-FREE



PHthalate FREE



FIRE-RESISTANT

INK PRINTABILITY



UV



LATEX

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	220g/sq.m	6.5oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	
Weave Method	N/A	Warp-knitted	
Shielding Rate	ANSI PH2.19, ISO 5/2	84%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Tensile Strength	DIN EN ISO 1421	409x550 N/5m	47x63 lbs/inch
Tear Strength	DIN 53363	75x95 N	17x21 lbs
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

