

Super Tenacity Tent Fabric

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-302D

BRIEF DESCRIPTION

- 100% polyester fabric with 600D x 600D woven base, matte
- Super strong tensile, tear strength & water resistance feature, making it perfect as tent fabric

FEATURES



PVC-FREE



PHthalate FREE



WATER-PROOF

INK PRINTABILITY



MATERIAL DETAILS

| PROPERTIES | TEST METHOD | METRIC | IMPERIAL |
|--------------------------------|---------------------------------|-------------------------------|---------------|
| Total Weight | DIN EN ISO 2286-2, ASTM D751 | 270 g/sq.m | 7.9 oz/sq.yd |
| Base Fabric | DIN 60001, ASTM D7641 | 100%polyester | 100%polyester |
| Yarn Dtex | DIN EN ISO 2060, ASTM D1907 | 660x660 dtex | 600x600denier |
| Weave Method | N/A | Woven | |
| Shrinkage | 210 °C, 30s | ≤3% | |
| Flame Resistance | DIN 4102-1-B1, NFPA 701 Test1 | DIN 4102-1-B1, NFPA 701 Test1 | |
| Recommend Fixation Temperature | N/A | 190 °C, 30s | |
| Width Available | DIN EN ISO 3759, ASTM D751-2006 | Max 320cm | 126" |
| Standard Length | DIN EN ISO 3759, ASTM D751-2006 | 50m | 55yds |

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.