

# **Classic Textile Wall Covering**

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-704T/ST-704D

### **BRIEF DESCRIPTION**

- New warp-knitted textile wall covering with grey rough back which has great flatness
- Always used in conjunction with glue, easy to operate
- With excellent opacity, can be used on the wall with any background color

## **FEATURES**







## **INK PRINTABILITY**





## **MATERIAL DETAILS**

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	280 g/sq.m	8.3 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Warp-knitted	
Shrinkage	210℃, 30s	≤3%	
Shielding Rate	ANSI PH2.19, ISO 5/2	96%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190℃, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Up to 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







